# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

# **SAFETY DATA SHEET**

Date of issue/Date of revision

: 25 October 2023

Version : 1.05



## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier		
Product name	: JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY	
Product code	: 17000DUT079	
Product description	:	
Product type	: Liquid.	
Other means of	: 00423201; 00423202; 00423204; 00423205; 00423206; 00423207; 00423208;	
identification	00423209; 00423210; 00423211; 00423212; 00423213; 00423215; 00423216; 00423217; 00423218; 00423219	
1.2 Relevant identified use	es of the substance or mixture and uses advised against	
Product use	: Consumer applications, Professional applications, Used by spraying, Application by non spray methods	
Use of the substance/ mixture	: Coating.	

#### **1.3 Details of the supplier of the safety data sheet**

PPG Architectural Coatings UK Ltd, Huddersfield Road, Birstall, West Yorkshire WF17 9XA, Tel: +44 (0) 1924 354000 PPG Europe BV, Oceanenweg 2, 1047 BB Amsterdam, Netherlands. Tel: +31 (0) 204 075 050

e-mail address of person	: ps.acemea-north@ppg.com
responsible for this SDS	

#### 1.4 Emergency telephone number

#### Supplier

+44 (0) 1924 354000 (Monday-Thursday 8.00-17.00, Friday 8.00-16.00 (GMT))

### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture			
Product definition	: Mixture		
Classification according	to UK CLP/GHS		
Not classified.			

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
General	:	Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P102, P101, P501

Code	: 17000DUT079	Date of issue/Date of revision	: 25 October 2023		
JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY					

# SECTION 2: Hazards identification

Supplemental label elements	:	Contains 1,2-benzisothiazol-3(2H)-one, octhilinone (ISO) and 2-methylisothiazol-3 (2H)-one. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	ts
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

# **SECTION 3: Composition/information on ingredients**

Mixture

Product/ingredient name	Identifiers	%	Classification	Туре
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.10	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]
octhilinone (ISO)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.0025	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	[1]
2-methylisothiazol-3(2H)-one	REACH #: 01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.010	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
English (GB)	United K	(ingdom (UK)		2/

Code	: 17000DUT079	Date of i
JOHNSTONE	S TRADE STORMS	HIELD SMOOTH MASONRY

Date of issue/Date of revision

: 25 October 2023

### SECTION 3: Composition/information on ingredients

EUH071	
See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. Type

[1] Substance classified with a health or environmental hazard

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sy</u>	<u>imptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any imm	nediate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled. **Specific treatments** 

: No specific treatment.

Code	: 17000DUT079	Date of issue/Date of revision	: 25 October 2023
JOHNSTON	ES TRADE STORMSHIELD SMOOTH	MASONRY	

# SECTION 5: Firefighting measures

		,
5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising	from	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	(	Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	1	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters		Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

mode.

· · · · · · · · · · · · · · · · · · ·		
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	-	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Code : 17000DUT079

Date of issue/Date of revision

: 25 October 2023

JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	1	Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **Occupational exposure limits**

No exposure limit value known.

**Recommended monitoring procedures**: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m <sup>3</sup>	Workers	Systemic
2-methylisothiazol-3(2H)-one	DNEL	Long term Inhalation	0.021 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.021 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.027 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.043 mg/m³	General population	Local
	DNEL	Short term Inhalation	0.043 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Oral	0.053 mg/kg bw/day	General population	Systemic

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

English (GB)

Code	:	17000DUT079	Date of issue/Date of revision	: 2	5 October 2023
JOHNSTON	E٤	S TRADE STORMSHIELD SMOOTH N	IASONRY		

### **SECTION 8: Exposure controls/personal protection**

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, befo eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and sa showers are close to the workstation location.	g.
Eye/face protection Skin protection	Safety glasses with side shields.	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard shoul- worn at all times when handling chemical products if a risk assessment indicates th necessary.	
Gloves	For prolonged or repeated handling, use the following type of gloves:	
	Recommended: Viton®	
Body protection	Personal protective equipment for the body should be selected based on the task t performed and the risks involved and should be approved by a specialist before handling this product.	being
Other skin protection	Appropriate footwear and any additional skin protection measures should be select based on the task being performed and the risks involved and should be approved specialist before handling this product.	
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If wor are exposed to concentrations above the exposure limit, they must use appropriate certified respirators. Use a properly fitted, air-purifying or air-fed respirator comply with an approved standard if a risk assessment indicates this is necessary. Wear respirator conforming to EN140. Filter type: organic vapour (Type A) and particula filter P3	ə, ing a
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensur they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipme will be necessary to reduce emissions to acceptable levels.	Э

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>							
Physical state	: Liqui	d.					
Colour	: Vario	ous					
Odour	: Odou	urless.					
Odour threshold	: Not a	available.					
Melting point/freezing point		: May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -4.21°C (24.4°F)					
Initial boiling point and boiling range	: >37.	78°C (>100°F)	)				
Flammability (solid, gas) Upper/lower flammability or explosive limits	: Grea	<ul> <li>liquid</li> <li>Greatest known range: Lower: 0.6% Upper: 4.2% (isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol)</li> </ul>					
Flash point	: Clos	ed cup: Not ap	oplicable.				
Auto-ignition temperature	:						
Ingredient name		°C	°F	Method			
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol		393	739.4				

Decomposition temperature	
рН	: 8.5

English (GB)

6/12

Code	: 17000DUT079	Date of issue/Date of revision	: 25 October 2023		
JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY					

# **SECTION 9: Physical and chemical properties**

÷

Viscosity	: Kinematic (40°C): >21 mm²/s			
Solubility(ies)	1 (Fig. 1) (			
Media	Result			
cold water	Partially soluble			
Miscible with water	: Yes.			

# Partition coefficient: n-octanol/ : Not applicable. water

#### Vapour pressure

	Va	apour Pres	sure at 20°C	V	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: 1.4		I				
Vapour density			value: 7.5 (Air = pentane-1,3-diol).	1) (isobutyric a	icid, monoe	ester with	
Explosive properties		•	self is not explosive with air is possible		ation of an e	explosible mixture of	
Oxidising properties Particle characteristics	: Pro	duct does r	not present an oxic	lizing hazard.			
Median particle size	: Not	applicable					

# SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients	<u> </u>
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition produce Refer to protective measures listed in sections 7 and 8.	ucts.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.	
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides	

# **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Result Species		Exposure	
1,2-benzisothiazol-3(2H)-	LC50 Inhalation Dusts and	Rat	0.4 mg/l	4 hours	
one	mists				
	LD50 Oral	Rat	1020 mg/kg	-	
octhilinone (ISO)	LC50 Inhalation Dusts and	Rat	0.27 mg/l	4 hours	
	mists LD50 Dermal	Rabbit	311 mg/kg	_	
	LD50 Oral	Rat	125 mg/kg	-	
2-methylisothiazol-3(2H)-	LC50 Inhalation Dusts and	Rat	0.19 mg/l	4 hours	
one	mists		5		
English (GB)	United K	ingdom (UK)	•		

#### Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code : 17000DUT079 Date of issue/Date of revision : 25 October 2023 JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY

## **SECTION 11: Toxicological information**

 9.000			
LD50 Dermal	Rat	242 mg/kg	-
LD50 Oral	Rat - Male	235 mg/kg	-

: There are no data available on the mixture itself. **Conclusion/Summary** 

### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one	1020	N/A	N/A	N/A	0.4
octhilinone (ISO)	125	311	N/A	N/A	0.27
2-methylisothiazol-3(2H)-one	235	242	N/A	N/A	0.19

#### Irritation/Corrosion

Conclusion/Summary	: Not available.
Skin	: There are no data available on the mixture itself.

skin

skin

Eyes

: There are no data available on the mixture itself. : There are no data available on the mixture itself.

Respiratory Sensitisation

**Product/ingredient name Route of Species** Result exposure JOHNSTONES TRADE skin Mouse Not sensitizing STORMSHIELD SMOOTH MASONRY

Sensitising

Sensitising

octhilinone (ISO) **Conclusion/Summary** 

1,2-benzisothiazol-3(2H)-one

Skin

: 429 Skin Sensitisation: Local Lymph Node Assay

Mouse

Guinea pig

: There are no data available on the mixture itself.

### Respiratory **Mutagenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

#### **Carcinogenicity**

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Teratogenicity	
<b>Conclusion/Summary</b>	1 ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (

There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

### Information on likely routes : Not available.

#### of exposure Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

English (GB)

Code : 17000DUT079	Date of issue/Date of revision : 25 October 2023		
JOHNSTONES TRADE STOR	RMSHIELD SMOOTH MASONRY		
SECTION 11: Toxico	logical information		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Symptoms related to the phy	vsical, chemical and toxicological characteristics		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delayed and immediate effect	cts as well as chronic effects from short and long-term exposure		
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health eff	ects		
Not available.			
Conclusion/Summary	: Not available.		
General	: No known significant effects or critical hazards.		
Carcinogenicity	: No known significant effects or critical hazards.		
Mutagenicity	: No known significant effects or critical hazards.		
Reproductive toxicity	: No known significant effects or critical hazards.		

#### Other information

: Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.11 mg/l Chronic NOEC 0.09 mg/l	Algae Fish - Trout	72 hours 28 days
Conclusion/Summary	: Not available.		

# Conclusion/Summary

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
1,2-benzisothiazol-3(2H)-one	0.7	-	Low
octhilinone (ISO)	2.45	-	Low

#### 12.4 Mobility in soil

Code : 17000DUT079 Date of issue/Date of revision : 25 October 2023 JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY

### SECTION 12: Ecological information

Soil/water partition : Not available. coefficient (Koc) **Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	<ul> <li>Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.</li> </ul>

#### Waste catalogue

	Waste designation
08 01 12 wa	aste paint and varnish other than those mentioned in 08 01 11

#### Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue	
Container	15 01 06	mixed packaging
Special precautions	This material and its container must be disposed of in a safe way. Empty contain or liners may retain some product residues. Avoid dispersal of spilt material and	

runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
English (0	GB)	United Kingdom	(UK)	10/12

Code : 17000DUT079 JOHNSTONES TRADE STORMSHIELD SMOO		Date of issue/Date of revision: 25 October 2023OTH MASONRY			
SECTION 1	I4: Transp	oort informa	tion		
Marine pollutant Not substances		t applicable.	Not applicable.	Not applicable.	Not applicable.
Additional info	ormation				
ADN IMDG IATA	: None ide	The product is only regulated as a dangerous good when transported in tank vessels. None identified. None identified.			
14.6 Special pr user	ecautions for	upright and se	-	always transport in closed ons transporting the produ	
	14.7 Transport in bulk : Not available according to IMO instruments				

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

#### Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

#### **Ozone depleting substances**

Not listed.

VOC for Ready-for-Use Mixture	: IIA/c. Exterior walls of mineral substrate. EU limit values: 40 g/l (2010.) This product contains a maximum of 3 g/l VOC.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Sovoso Directivo	

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration PRN = REACH Registration Number</li> </ul>
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification

Code : 17000DUT079

Date of issue/Date of revision

: 25 October 2023

JOHNSTONES TRADE STORMSHIELD SMOOTH MASONRY

### **SECTION 16: Other information**

Not classified.

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

#### **History**

Date of issue/ Date of revision	: 25 October 2023
Date of previous issue	: 11 October 2023
Prepared by	: EHS
Version	: 1.05

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.